

a portable multimedia player (PMP), or a navigation device. In this disclosure, the terms 'module' and 'unit' can be used interchangeably.

[0028] FIG. 1 illustrates a block diagram of a mobile terminal **100** according to an embodiment of the present invention. Referring to FIG. 1, the mobile terminal **100** may include a wireless communication unit **110**, an audio/video (A/V) input unit **120**, a user input unit **130**, a sensing unit **140**, an output unit **150**, a memory **160**, an interface unit **170**, a controller **180**, and a power supply unit **190**. Two or more of the wireless communication unit **110**, the A/V input unit **120**, the user input unit **130**, the sensing unit **140**, the output unit **150**, the memory **160**, the interface unit **170**, the controller **180**, and the power supply unit **190** may be incorporated into a single unit, or some of the wireless communication unit **110**, the A/V input unit **120**, the user input unit **130**, the sensing unit **140**, the output unit **150**, the memory **160**, the interface unit **170**, the controller **180**, and the power supply unit **190** may be divided into two or more smaller units.

[0029] The wireless communication unit **110** may include a broadcast reception module **111**, a mobile communication module **113**, a wireless internet module **115**, a short-range communication module **117**, and a global positioning system (GPS) module **119**.

[0030] The broadcast reception module **111** may receive a broadcast signal and/or broadcast-related information from an external broadcast management server through a broadcast channel. The broadcast channel may be a satellite channel or a terrestrial channel. The broadcast management server may be a server which generates broadcast signals and/or broadcast-related information and transmits the generated broadcast signals and/or the generated broadcast-related information or may be a server which receives and then transmits previously-generated broadcast signals and/or previously-generated broadcast-related information.

[0031] The broadcast-related information may include broadcast channel information, broadcast program information and/or broadcast service provider information. The broadcast signal may be a TV broadcast signal, a radio broadcast signal, a data broadcast signal, the combination of a data broadcast signal and a TV broadcast signal or the combination of a data broadcast signal and a radio broadcast signal. The broadcast-related information may be provided to the mobile terminal **100** through a mobile communication network. In this case, the broadcast-related information may be received by the mobile communication module **113**, rather than by the broadcast reception module **111**. The broadcast-related information may come in various forms. For example, the broadcast-related information may be electronic program guide (EPG) of digital multimedia broadcasting (DMB) or may be electronic service guide (ESG) of digital video broadcast-handheld (DVB-H).

[0032] The broadcast reception module **111** may receive the broadcast signal using various broadcasting systems such as digital multimedia broadcasting-terrestrial (DMB-T), digital multimedia broadcasting-satellite (DMB-S), media forward link only (MediaFLO), DVB-H, and integrated services digital broadcast-terrestrial (ISDB-T). In addition, the broadcast reception module **111** may be configured to be suitable for nearly all types of broadcasting systems other than those set forth herein. The broadcast signal and/or the broadcast-related information received by the broadcast reception module **111** may be stored in the memory **160**.

[0033] The mobile communication module **113** may transmit wireless signals to or receives wireless signals from at least one of a base station, an external terminal, and a server through a mobile communication network. The wireless signals may include various types of data according to whether the mobile terminal **100** transmits/receives voice call signals, video call signals, or text/multimedia messages.

[0034] The wireless internet module **115** may be a module for wirelessly accessing the internet. The wireless internet module **115** may be embedded in the mobile terminal **100** or may be installed in an external device. The wireless internet module **115** may be embedded in the mobile terminal **100** or may be installed in an external device. The wireless internet module **115** may use various wireless internet technologies such as wireless local area network (WLAN), Wireless Broadband (WiBro), World Interoperability for Microwave Access (Wimax), and High Speed Downlink Packet Access (HSDPA).

[0035] The short-range communication module **117** may be a module for short-range communication. The short-range communication module **117** may use various short-range communication techniques such as Bluetooth, radio frequency identification (RFID), infrared data association (IrDA), ultra wideband (UWB), and ZigBee.

[0036] The GPS module **119** may receive position information from a plurality of GPS satellites.

[0037] The A/V input unit **120** may be used to receive audio signals or video signals. The A/V input unit **120** may include a camera **121** and a microphone **123**. The camera **121** may process various image frames such as still images or moving images captured by an image sensor in a video call mode or an image capturing mode. The image frames processed by the camera **121** may be displayed by a display module **151**.

[0038] The image frames processed by the camera **121** may be stored in the memory **160** or may be transmitted to an external device through the wireless communication unit **110**. The mobile terminal **100** may include two or more cameras **121**.

[0039] The microphone **123** may receive external sound signals during a call mode, a recording mode, or a voice recognition mode with the use of a microphone and may convert the sound signals into electrical sound data. In the call mode, the mobile communication module **113** may convert the electrical sound data into data that can be readily transmitted to a mobile communication base station and then output the data obtained by the conversion. The microphone **123** may use various noise removal algorithms to remove noise that may be generated during the reception of external sound signals.

[0040] The user input unit **130** may generate key input data based on user input for controlling the operation of the mobile terminal **100**. The user input unit **130** may be implemented as a keypad, a dome switch, a touch pad (static pressure/static voltage), a jog wheel, or a jog switch. In particular, if the user input unit **130** is implemented as a touch pad and forms a layer structure together with the display module **151**, the user input unit **130** and the display module **151** may be collectively referred to as a touch screen.

[0041] The sensing unit **140** determines a current state of the mobile terminal **100** such as whether the mobile terminal **100** is opened up or closed, the position of the mobile terminal **100** and whether the mobile terminal **100** is placed in contact with a user, and generates a sensing signal for controlling the operation of the mobile terminal **100**. For example, when the